Equipment Monitoring Log Form: Refrigerated Condenser (Washer)

Refrigerated Condenser used for Washer

Date	Inspector's Initials	Machine No.	Inlet Temp	Outlet Temp	Temperature Difference	Is Temp Difference < 20°F/11.1°C
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No
						Yes / No

Temp Difference= Inlet Temp - Outlet Temp

If the temperature difference is less than 20°F/11.1°C, attach a completed corrective action report.

Measurements of the inlet and outlet streams shall be with a temperature sensor. Each temperature sensor shall be used according to the manufacturer's instructions, and designed to measure at least a temperature range from 32°F/0°C to 120°F/48.9°C to an accuracy of 2°F/1.1°C.

AristoCraft, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose. ARISTOCRAFT, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, ARISTOCRAFT, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.